Forest Products Journal Index . . . 1963

Articles are listed in three ways: by title, by subject, and by author. Combined title and subject listings appear first. Titles are listed alphabetically, with leading articles *A, An,* and *The* omitted. Whenever possible, subject listings are grouped under title of the Society's 11 Subject-Matter Divisions, with the Division's title printed in boldface capital letters, and appropriate subdivisions printed in upper and lower case boldface. Where appropriate, additional boldface headings have been included and many articles have been cross-referenced under several headings.

The Author Index contains an entry for every author, with complete information listed under the senior author; listings for co-authors refer back to the senior author.

Reprints of all articles listed in the index may be obtained. The reprint order number and the cost per single copy are listed in the Author Index. Prices are based on 20 cents per printed page, with a $1.50 maximum charge per reprint. Special bulk rates are available. Check or money order must accompany all orders.

FPRS Title and Subject Index . . . Vol. XIII, 1963

A

Abnormal Wood in Yellow Poplar: *Liriodendron Tulipifera* L., A. C. Barefoot Jr., 1: 16.

Accelerated Drying of Lodgepole Pine and Western Larch Poles, D. P. Lowery and E. F. Rasmussen, 6: 221.

After Lumber — What Other Products — Why?, H. B. McKean, 5: 180.

Analysis of Creosote by Infrared Spectroscopy, R. W. Drisko, 4: 156.

Analysis of the Productive Capacity of Sawmill Headrigs, T. A. Lambe, 11: 499.

ANATOMY AND FUNDAMENTAL PROPERTIES

Biological Properties

Conidendrin in the Floccosoids of Western Hemlock, G. M. Barton, 7: 304.

Chemical Properties

Characteristics of a Phlobaphene from Western Red Cedar Bark, E. P. Swan, 5: 195.

Color Precursors in Douglas-Fir, G. M. Barton, and J. A. F. Gardner, 6: 216.

Physical Properties

Abnormal Wood in Yellow Poplar: *Liriodendron Tulipifera* L., A. C. Barefoot Jr., 1: 16.

Effect of Water Storage on Electrical Resistance of Wood, A. R. Katz and D. G. Miller, 7: 255.

Mechanism of Check Formation, Arno P. Schniewind, 11: 475.

Mechanism of Electrical Conduction in Wood, J. H. Brown, R. W. Davidson, and C. Skaar, 10: 455.

Moisture Diffusion Coefficients in Wood as Calculated from Adsorption, Desorption, and Steady State Data, G. L. Comstock, 3: 97.

Movement of Moisture through a Softwood in the Hygroscopic Range, E. T. Choong, 11: 489.

Permeability of Wood to Fluids, A. J. Stamm, 11: 503.

Piezoelectric Effect in Wood, W. L. Galligan and L. D. Bertholf, 12: 517.

Selected Wood Characteristics of Young Yellow Poplar (*Liriodendron tulipifera* L.), II: Shrinkage of Normal and Abnormal Wood, 10: 443.

Significance of Microshrinkage During the Initial Stages of Drying, J. G. Haygreen, 12: 533.

Specific Heat and Conductivity of Particle-Board as Functions of Temperature, R. J. Ward and C. Skaar, 1: 31.

Spiral Grain in Trees, A Review, A. F. Noskowiak, 7: 266.

Thermal Properties of Bark, R. E. Martin, 10: 419.

Wood Structure

Cell-Wall Crystallinity as a Function of Tensile Strain, W. K. Murphey, 4: 151.

Cell-Wall Model, E. A. Behr, 4: 168.

Characteristics of Tracheids Produced in Gamma and Gamma-Neutron Environment, J. R. Hamilton, 2: 62.

Internal Moisture Stress and Wood Formation in Conifers, R. Zahner, 6: 240.

Peculiarity of Compression of Conifers in Radial Direction, J. Bodig, 10: 438.

Selected Wood Characteristics of Young Yellow Poplar, A. C. Barefoot, Jr., 6: 233.

Siliceous Skeletons of Wood Fibers, R. M. Chatters, 9: 368.

Time-Related Flexural Behavior of Small Douglas-Fir Beams Under Prolonged Loading, R. L. Youngs and H. C. Hilbrand, 6: 227.

Annual Review of Lignin Chemistry, I. A. Pearl, 9: 373.

Aspen Bark as a Source of Organic Chemicals, I. A. Pearl, 3: 122.

Asymmetrical Permeability of Composite Laminates, H. Tarkow, 8: 318.

B

Bark

Aspen Bark as a Source of Organic Chemicals, I. A. Pearl, 3: 122.

Fortified Bark for Mulching and Soil Conditioning, W. B. Bollen and D. W. Glennie, 6: 209.

Thermal Properties of Bark, R. E. Martin, 10: 419.

Beetle Scars in Philippine Mahogany, G. N. Arneson, 4:149.

Bright Future for Wood Engineering, A. P. Schniewind, 8: 323.

C

Casein-Dialehyde Starch Adhesive for Wood, F. P. Weakley, M. L. Ashby, and C. L. Mehltretter, 2: 51.

Cell-Wall Crystallinity as a Function of Tensile Strain, W. K. Murphey, 4: 151.

Cell-Wall Model, E. A. Behr, 4: 168.

Characteristics of a Phlobaphene from Western Red Cedar Bark, E. P. Swan, 5: 195.

Characteristics of Tracheids Produced in Gamma and Gamma-Neutron Environment, J. R. Hamilton, 2: 62.

Charcoal: See Chemical Conversion.

Charcoal Production by a Fluid-Bed Process, D. G. Kilburn and B. H. Levelton, 10: 427.

CHEMICAL CONVERSION

Annual Review of Lignin Chemistry, I. A. Pearl, 9: 373.

Progress in Chemical Conversion, J. W. Rowe, 7: 276.

Derived Products

Aspen Bark as a Source of Organic Chemicals, I. A. Pearl, 3: 122.

Fortified Bark for Mulching and Soil Conditioning, W. B. Bollen and D. W. Glennie, 6: 209.

Impact of Naval Stores on Utilization of Longleaf and Slash Pine Timber, R. H. Page, 9: 361.

Investigation of Solvent Extractives from NSSC Black Liquor, W. A. Biggs, W. R. Cook, and I. A. Pearl, 10: 433.

Reactions of Ethyleneimine with Alkali Lignins, J. B. Doughty, 9: 413.

Modification

Characteristics of a Phlobaphene from Western Red Cedar Bark, E. P. Swan, 5: 195.

Charcoal Production by a Fluid-Bed Process, D. G. Kilburn and B. H. Levelton, 10: 427.

Pulping

Color Precursors in Douglas-Fir, G. M. Barton and J. A. F. Gardner, 6: 216.

Color Precursors in Douglas-Fir, G. M. Barton and J. A. F. Gardner, 6: 216.

Compressibility and Bond Quality of Western Softwood Veneers, R. A. Currier, 2: 71.

Conidendrin in the Floccosoids of Western Hemlock, G. M. Barton, 7: 304.

Consolidation & Refinement Mark Progress in Glues & Gluing, C. B. Hemming, 2: 45.

Construction: See Wood Engineering.

Continuous Lamination of Lumber, N. Malarkey Jr., 2: 68.

Cutting Wood with Water Jets, University of Michigan project, 3: 121.

D

Design of Plywood Folded Plates, D. H. Brown, 4: 131.

Developments in Wood Drying, C. J. Kozlik, 1:1.

Diffusion Coefficients

Moisture Diffusion Coefficients in Wood as Calculated from Adsorption, Desorption, and Steady State Data, G. L. Comstock, 3: 97.

Dimensional Stabilization: See also Treatments and Coatings.

Dimensional Stabilization with Polymerizable Vapor of Ethylene Oxide, C. W. McMillin, 2: 56.

Effect of Treating Conditions on Dimensional Behavior of Wood During Polyethylene Glycol Soak Treatments, D. L. Kenaga, 8: 345.

PEG-Treated Walnut Limbwood Makes Handsome Decorator Clock, H. L. Mitchell, 9: 416.

Studies on Predrying and Polyethylene Glycol Treatment of Green Oak, H. A. Huber and A. W. Klimaszewski, 10: 430.

Dimensional Stabilization with Polymerizable Vapor of Ethylene Oxide, C. W. McMillin, 2: 56.

Douglas-Fir

Color Precursors in Douglas-Fir, G. M. Barton and J. A. F. Gardner, 6: 216.

Effect of Heat Treatment on the Surface of Douglas-Fir Veneer, W. V. Hancock, 2: 81.

Time-Related Flexural Behavior of Small Douglas-Fir Beams Under Prolonged Loading, R. L. Youngs and H. C. Hilbrand, 6: 227.

DRYING

Developments in Wood Drying, C. J. Kozlik, 1: 1.

Drying in Russia: Research and Practice, H. Kübler, 12: 562.

Kiln Drying

Accelerated Drying of Lodgepole Pine and Western Larch Poles, D. P. Lowery and E. F. Rasmussen, 6: 221.

Quality and Strength Properties of Douglas-Fir Dried at High Temperatures, M. Salamon, 8: 339.

Role of Temperature in the Relief of Drying Stresses, D. E. Nelson, 3:124.

Small Dry Kiln, J. P. Howe and W. S. McNamara, 9: 417.

Surface Checking of White Oak As Related to Mechanical Processing, L. I. Gaby, 12: 529.

Moisture-Use Relationship

Effect of Moisture Content on Strength of Bolted Timber Connection, J. Longworth and A. E. McMullin, 3: 104.

Effect of Organic Liquids on Collapse and Shrinkage of Wood, I: Effect of Degree of Replacement, E. L. Ellwood and B. A. Ecklund, 7: 291.

Effect of Organic Liquids on Collapse and Shrinkage of Wood, II: Effect of Drying Temperature, E. L. Ellwood and B. A. Ecklund, 8: 350.

Effect of Organic Liquids on Collapse and Shrinkage of Wood, III: Chemical Influences, E. L. Ellwood, B. A. Ecklund, and Eugene Zavarin, 9: 401.

Effect of Water Storage on Electrical Resistance of Wood, A. R. Katz and D. G. Miller, 7: 255.

How Durable is Particleboard? —Part II: Effect of Temperature and Humidity, R. A. Hann, J. M. Black, and R. F. Blomquist, 5: 169.

Internal Moisture Stress and Wood Formation in Conifers, R. Zahner, 6: 240.

Mechanism of Check Formation, Arno P. Schniewind, 11: 475.

Moisture Content Determination for Wood with Highly Volatile Constituents, Helmuth Resch and B. A. Ecklund, 11: 481.

Moisture Diffusion Coefficients in Wood as Calculated from Adsorption, Desorption, and Steady State Data, G. L. Comstock, 3: 97.

Movement of Moisture through a Softwood in the Hygroscopic Range, E. T. Choong, 11: 489.

PEG-Treated Walnut Limbwood Makes Handsome Decorator Clock, H. L. Mitchell, 9: 416.

Permeability of Wood to Fluids, A. J. Stamm, 11:503.

Selected Wood Characteristics of Young Yellow Poplar (*Liriodendron tulipifera* L.), II: Shrinkage of Normal and Abnormal Wood, 10: 443.

Significance of Microshrinkage During the Initial Stages of Drying, J. G. Haygreen, 12: 533.

Studies on Predrying and Polyethylene Glycol Treatment of Green Oak, H. A. Huber and A. W. Klimaszewski, 10: 430.

Transverse Shrinkage of Wood, W. C. Stevens, 9: 386.

Special Products

New Method for Selecting Glues for R. F. Heating, J. F. S. Carruthers, 5: 190.

Veneer Drying

Compressibility and Bond Quality of Western Softwood Veneers, R. A. Currier, 2: 71.

Effect of Heat Treatment on the Surface of Douglas-Fir Veneer, W. V. Hancock, 2: 81.

High Speed Drying of Western Softwoods for Exterior Plywood, F. H. Milligan and R. D. Davies, 1: 23.

Ventilating Veneer Dryers, S. E. Corder, 10: 449.

Drying in Russia: Research and Practice, H. Kübler, 12: 562.

Dual-Linear Micrometer, J. R. Hamilton, 2: 70.

Durability of R. F. Cured Urea Bonds, R. W. Peterson, 5: 187.

E

Economic Importance of Timber in the United States, D. Hair, 9: 355.

Effect of a Mold, *Trichoderma Viride*, On Decay of Birch by Four Storage-Rot Fungi, J. K. Shields and E. A. Atwell, 7: 262.

Effect of Gamma Radiation of Decay Resistance of Wood, T. C. Scheffer, 5: 208.

Effect of Heat Treatment on the Surface of Douglas-Fir Veneer, W. V. Hancock, 2: 81.

Effect of Joint Geometry on Tensile Strength of Finger Joints, M. L. Selbo, 9: 390.

Effect of Moisture Content on Strength of Bolted Timber Connection, J. Longworth and A. E. McMullin, 3: 104.

Effect of Organic Liquids on Collapse and Shrinkage of Wood, I: Effect of Degree of Replacement, E. L. Ellwood and B. A. Ecklund, 7: 291.

Effect of Organic Liquids on Collapse and Shrinkage of Wood, II: Effect of Drying Temperature, E. L. Ellwood and B. A. Ecklund, 8: 350.

Effect of Organic Liquids on Collapse and Shrinkage of Wood, III: Chemical Influences, E. L. Ellwood, B. A. Ecklund, and Eugene Zavarin, 9: 401.

Effect of Treating Conditions on Dimensional Behavior of Wood During Polyethylene Glycol Soak Treatments, D. L. Kenaga, 8: 345.

Effect of Water Storage on Electrical Resistance of Wood, A. R. Katz and D. G. Miller, 7: 255.

Efficiency of Urea- and Phenol-Formaldehyde in Particleboard, M. Carroll, 3: 113.

Electric Characteristics

Effect of Water Storage on Electrical Resistance of Wood, A. R. Katz and D. G. Miller, 7: 255.

Mechanism of Electrical Conduction in Wood, J. H. Brown, R. W. Davidson, and C. Skaar, 10: 455.

Specific Heat and Conductivity of Particleboard as Functions of Temperature, R. J. Ward and C. Skaar, 1: 31.

End and Edge Gluing: See Glues and Gluing Processes.

Engineered Products: See Wood Engineering.

Ethylene Oxide

Dimensional Stabilization with Polymerizable Vapor of Ethylene Oxide, C. W. McMillin, 2: 56.

Ethyleneimine: See also Chemical Conversion

Reactions of Ethyleneimine with Alkali Lignins, J. B. Doughty, 9: 413.

Evaluating Log and Tree Quality for Wood Products, P. H. Lane, 3: 89.

Experimental Analysis of Wood Cutting Tool Stresses, C. D. Mote, 5: 203.

Exploratory Experiments on the Possible Use of Radioactive Waste Materials in Wood Industries, N. C. Franz, 3: 94.

Extractives: See also Chemical Conversion

Investigation of Solvent Extractives from NSSC Black Liquor, W. A. Biggs, W. R. Cook, and I. A. Pearl, 10: 433.

F

Finger Joints: See also Glues & Gluing Processes and Wood Engineering

Effect of Joint Geometry on Tensile Strength of Finger Joints, M. L. Selbo, 9: 390.

Improved Tips for Finger Joints, D. B. Richards, 6: 250.

Finishing: See Treatments & Coatings

Floccosoids

Conidendrin in the Floccosoids of Western Hemlock, G. M. Barton, 7: 304.

Folded Plates: See also Wood Engineering and Glues and Gluing.

Design of Plywood Folded Plates, D. H. Brown, 4: 131.

Forest Economics: See Timber Production.

Fortified Bark for Mulching and Soil Conditioning, W. B. Bollen and D. W. Glennie, 6: 209.

Fumigation May End Oak Embargoes, T. W. Jones, 12: 564.

G

Gamma Rays

Characteristics of Tracheids Produced in Gamma and Gamma-Neutron Environment, J. R. Hamilton, 2: 62.

Effect of Gamma Radiation on Decay Resistance of Wood, T. C. Scheffer, 5: 208.

Gluability of Fire-Retardant Treated Wood, E. G. Bergin, 12: 549.

Glue Lam: See Glues and Gluing Processes.

GLUES AND GLUING PROCESSES

Consolidation & Refinement Mark Progress in Glues & Gluing, C. B. Hemming, 2: 45.

Durability of R. F. Cured Urea Bonds, R. W. Peterson, 5: 187.

New Method for Selecting Glues for R. F. Heating, J. F. S. Carruthers, 5: 190.

Surface Texture Measurements, D. A. Stumbo, 7: 299.

Adhesives

Casein-Dialdehyde Starch Adhesive for Wood, F. P. Weakley, M. L. Ashby, and C. L. Mehltretter, 2: 51.

Efficiency of Urea- and Phenol-Formaldehyde in Particleboard, M. Carrol, 3: 113.

Gluability of Fire-Retardant Treated Wood, E. G. Bergin, 12: 549.

Assemblies

Effect of Joint Geometry on Tensile Strength of Finger Joints, M. L. Selbo, 9: 390.

End- and Edge-Gluing

Continuous Lamination of Lumber, N. Malarkey, Jr., 2: 68.

Glue Lam

New Method for Testing Glue Joints of Laminated Timbers, M. L. Selbo, 3: 93.

Production and Marketing of Plywood Structural Components, K. M. Watson, 8: 319.

Sandwich Construction

Improved Tips for Finger Joints, D. B. Richards, 6: 250.

Roll Gluing of Exterior Overlays, A. L. Mottet, D. Burnet, R. Casselman, and E. Heller, 5: 175.

Veneers and Plywood

Beetle Scars in Philippine Mahogany, G. N. Arneson, 4: 149.

Compressibility and Bond Quality of Western Softwood Veneers, R. A. Currier, 2: 71.

Design of Plywood Folded Plates, D. H. Brown, 4: 131.

High Speed Drying of Western Softwoods for Exterior Plywood, F. H. Milligan and R. D. Davies, 1: 23.

Technical Considerations for Manufacturing Southern Pine Plywood, H. O. Fleischer and J. F. Lutz, 1: 39.

Veneer and Plywood, book review by H. O. Fleischer, 5: 186.

Weathering Resistance of Plywood Bonded and Coated with Phenol Formaldehyde, H. H. Bosshard and L. P. Futo, 12: 557.

H

Hemlock, Western

Conidendrin in the Floccosoids of Western Hemlock, G. M. Barton, 7: 304.

High-Energy Jets

Cutting Wood with Water Jets, University of Michigan project, 3: 121.

High Energy Jets as a New Concept in Wood Machining, E. L. Bryan, 8: 305.

High Energy Jets as a New Concept in Wood Machining, E. L. Bryan, 8: 305.

High Speed Drying of Western Softwoods for Exterior Plywood, F. H. Milligan and R. D. Davies, 1: 23.

High Temperature Drying: See Drying

How Durable is Particleboard?—Part II: Effect of Temperature and Humidity, R. A. Hann, J. M. Black, and R. F. Blomquist, 5: 169.

I

Impact of Naval Stores on Utilization of Longleaf and Slash Pine Timber, R. H. Page, 9: 361.

Improved Tips for Finger Joints, D. B. Richards, 6: 250.

Improvement and Automation, P. Heller, 3: 112.

Improvement of Sawmill Cutting Tool Sharp Life by Surface Hardening, H. N. Halvorson and W. M. Stuart, 3: 108.

Improving the Preparation of Glass Knives for Ultra-Microtomy, I. B. Sachs, 2: 80.

Industry-Education

After Lumber—What Other Products—Why?, H. B. McKean, 5: 180.

Cell-Wall Model, E. A. Behr, 4: 168.

Economic Importance of Timber in the United States, D. Hair, 9: 355.

Drying in Russia: Research and Practice, H. Kübler, 12: 562.

Exploratory Experiments on the Possible Use of Radioactive Waste Materials in Wood Industries, N. C. Franz, 3: 94.

Improving the Preparation of Glass Knives for Ultra-Microtomy, I. B. Sachs, 2: 80.

Integrated Marketing by Non-Integrated Timber Owners, M. P. Lazara, 4: 147.

Resource Allocation in the Wood Industry, P. J. Dyson, 8: 337.

Ten Ways to Up-Date Preventive Maintenance, T. J. Sievert, 4: 139.

Tomorrow's Houses from Trees of Today, O. C. Heyer, 6: 252.

Two Views on Research, R. J. Anderson and R. J. Seidl, 12: 525.

Influence of Certain Variables on Veneer-Cutting Behavior, R. B. Hoadley, 12: 538.

Infrared Spectroscopy

Analysis of Creosote by Infrared Spectroscopy, R. W. Drisko, 4: 156.

Integrated Marketing by Non-Integrated Timber Owners, M. P. Lazara, 4: 147.

Internal Moisture Stress and Wood Formation in Conifers, R. Zahner, 6: 240.

Investigation of Solvent Extractives from NSSC Black Liquor, W. A. Biggs, W. R. Cook, and I. A. Pearl, 10: 433.

K

Kiln Drying: See Drying.

L

Larch, Western

Accelerated Drying of Lodgepole Pine and Western Larch Poles, D. P. Lowery and E. F. Rasmussen, 6: 221.

Laser Cutting

Machining Wood with Light, E. L. Bryan, 1: 14.

Lignin: See also Chemical Conversion

Annual Review of Lignin Chemistry, I. A. Pearl, 9: 373.

Reactions of Ethyleneimine with Alkali Lignins, J. B. Doughty, 9: 413.

Longleaf Pine

Impact of Naval Stores on Utilization of Longleaf and Slash Pine Timber, R. H. Page, 9: 361.

Lumber and Lumber Manufacturing:

See Mechanical Conversion.

M

Machining Wood with Light, E. L. Bryan, 1: 14.

Maintenance

Ten Ways to Up-Date Preventive Maintenance, T. J. Sievert, 4: 319.

MARKETING

Distribution

Economic Importance of Timber in the United States, D. Hair, 9: 355.

Promotion

Production and Marketing of Plywood Structural Components, K. M. Watson, 8: 319.

Materials Handling: See Production Management.

MECHANICAL CONVERSION

Machining

Cutting Wood with Water Jets, University of Michigan project, 3: 121.

Experimental Analysis of Wood Cutting Tool Stresses, C. D. Mote, 5: 203.

High Energy Jets as a New Concept in Wood Machining, E. L. Bryan, 8: 305.

Improvement of Sawmill Cutting Tool Sharp Life by Surface Hardening, H. N. Halvorson and W. M. Stuart, 3: 108.

Machining Wood with Light, E. L. Bryan, 1: 14.

New Horizons in Bowl Turning, G. H. Englerth and H. L. Mitchell, 2: 48.

Surface Checking of White Oak As Related to Mechanical Processing, L. I. Gaby, 12: 529.

Sawing

Analysis of the Productive Capacity of Sawmill Headrigs, T. A. Lambe, 11: 499.

Veneer Cutting

Influence of Certain Variables on Veneer-Cutting Behavior, R. B. Hoadley, 12: 538.

Precompressing Flitches to Improve the Quality of Slicewood, J. F. Lutz, 6: 248.

Technical Considerations for Manufacturing Southern Pine Plywood, H. O. Fleischer and J. F. Lutz, 1: 39.

Mechanical Stress Grading

After Lumber—What Other Products—Why? H. B. McKean, 5: 180.

Mechanism of Check Formation, Arno P. Schniewind, 11: 475.

Mechanism of Electrical Conduction in Wood, J. H. Brown, R. W. Davidson, and C. Skaar, 10: 455.

Millwork, Exterior: See also Mechanical Conversion.

On-Site Preservative Treatments: Their Effectiveness for Exterior Millwork of Different Species Used in Various Climates, R. C. Scheffer, A. F. Verral and G. Harvey, 1: 7.

Overtreatment of Millwork: Is Control at the Log Pond Feasible?, M. D. MacPeak, 4: 142.

Moisture Content Determination for Wood with Highly Volatile Constituents, Helmuth Resch and B. A. Ecklund, 11: 481.

Moisture Diffusion Coefficients in Wood as Calculated from Adsorption, Desorption, and Steady State Data, G. L. Comstock, 3: 97.

Moisture-Use Relationship: See Drying.

Movement of Moisture through a Softwood in the Hygroscopic Range, E. T. Choong, 11: 489.

N

Naval Stores: See also Chemical Conversion.

Impact of Naval Stores on Utilization of Longleaf and Slash Pine Timber, R. H. Page, 9: 361.

New Horizons in Bowl Turning, G. H. Englerth and H. L. Mitchell, 2: 48.

New Method for Selecting Glues for R. F. Heating, J. F. S. Carruthers, 5: 190.

New Method for Testing Glue Joints of Laminated Timbers, M. L. Selbo, 3: 93.

Nondestructive Testing

After Lumber—What Other Products—Why?, H. B. McKean, 5: 180.

O

Oak

Studies on Predrying and Polyethylene Glycol Treatment of Green Oak, H. A. Huber and A. W. Klimaszewski, 10: 430.

On-Site Preservative Treatments: Their Effectiveness for Exterior Millwork of Different Species Used in Various Climates, R. C. Scheffer, A. F. Verral, and G. Harvey, 1:7.

Overlays: See also Glues and Gluing and Particle and Fiber Processes.

Roll Gluing of Exterior Overlays, A. L. Mottet, D. Burnet, R. Casselman, and E. Heller, 5: 175.

Overtreatment of Millwork: Is Control at the Log Pond Feasible?, M. D. MacPeak, 4: 142.

P

PARTICLE AND FIBER PROCESSES

Fortified Bark for Mulching and Soil Conditioning, W. B. Bollen and D. W. Glennie, 6: 209.

Some Engineering Considerations of of a Wood-Chip Pipeline, W. A. Hunt, 9: 365.

Surface Texture Measurements, D. A. Stumbo, 7: 299.

Flakeboard

Some Observations on the Development of a Laboratory Flakeboard Process, C. A. Hart and J. T. Rice, 11: 483.

Particleboard

Efficiency of Urea- and Phenol-Formaldehyde in Particleboard, M. Carroll, 3: 113.

How Durable is Particleboard?—Part II: Effect of Temperature and Humidity, R. A. Hann, J. M. Black, and R. F. Blomquist, 5: 169.

Specific Heat and Conductivity of Particleboard as Functions of Temperature, R. J. Ward and C. Skaar, 1: 31.

Wafer Dimension Control: Number One Design Criterion for Plant Producing Particleboard for Building Construction Uses, J. M. Gunn, 4: 163.

Plastic Laminates

Asymmetrical Permeability of Composite Laminates, H. Tarkow, 8: 318.

Roll Gluing of Exterior Overlays, A. L. Mottet, D. Burnet, R. Casselman, and E. Heller, 5: 175.

Weathering Resistance of Plywood Bonded and Coated with Phenol Formaldehyde, H. H. Bosshard and L. P. Futo, 12: 557.

Particleboard: See Particle and Fiber Processes

Peculiarity of Compression of Conifers in Radial Direction, J. Bodig, 10: 438.

PEG-Treated Walnut Limbwood Makes Handsome Decorator Clock, H. L. Mitchell, 9: 416.

Permeability of Wood to Fluids, A. J. Stamm, 11: 503.

Phenol-Formaldehyde: See also Glues and Gluing Processes and Particle and Fiber Processes.

Efficiency of Urea- and Phenol-Formaldehyde in Particleboard, M. Carroll, 3: 113.

Philippine Mahogany

Beetle Scars in Philippine Mahogany, G. N. Arneson, 4: 149.

Piezoelectric Effect in Wood, W. L. Galligan and L. D. Bertholf, 12: 517.

Pine, Lodgepole

Accelerated Drying of Lodgepole Pine and Western Larch Poles, D. P. Lowery and E. F. Rasmussen, 6: 221.

Pine, Southern

Technical Considerations for Manufacturing Southern Pine Plywood, H. O. Fleischer and J. F. Lutz, 1: 39.

Plant Layout: See Production Management.

Plastic Laminates: See Particle and Fiber Processes.

Plywood: See also Glues and Gluing Processes.

Polyethylene Glycol

Effect of Treating Conditions on Dimensional Behavior of Wood During Polyethylene Glycol Soak Treatments, D. L. Kenaga, 8: 345.

New Horizons in Bowl Turning, G. H. Englerth and H. L. Mitchell, 2: 48.

PEG-Treated Walnut Limbwood Makes Handsome Decorator Clock, H. L. Mitchell, 9: 416.

Studies on Predrying and Polyethylene Glycol Treatment of Green Oak, H. A. Huber and A. W. Klimaszewski, 10: 430.

Precompressing Flitches to Improve the Quality of Slicewood, J. F. Lutz, 6: 248.

Preservation: See Treatments and Coatings.

Production and Marketing of Plywood Structural Components, K. M. Watson, 8: 319.

Production Control: See Production Management.

PRODUCTION MANAGEMENT

Two Views on Research, R. J. Anderson and R. J. Seidl, 12: 525.

Automation

Improvement and Automation, P. Heller, 3: 112.

Materials Handling

Some Engineering Considerations of a Wood-Chip Pipeline, W. A. Hunt, 9: 365.

Quality Control

Analysis of Creosote by Infrared Spectroscopy, R. W. Drisko, 4: 156.

Surface Texture Measurements, D. A. Stumbo, 7: 299.

Ten Ways to Up-Date Preventive Maintenance, T. J. Sievert, 4: 139.

Tensile Strength Test for Comparative Evaluation of Wood Preservatives, F. L. Brown, 9: 405.

Work Measurements

Analysis of the Productive Capacity of Sawmill Headrigs, T. A. Lambe, 11: 499.

Plant Layout

Technical Considerations for Manufacturing Southern Pine Plywood, H. O. Fleischer and J. F. Lutz, 1: 39.

Wafer Dimension Control: Number One Design Criterion for Plant Producing Particleboard for Building Construction Uses, J. M. Gunn, 4: 163.

Production Control

Charcoal Production by a Fluid-Bed Process, D. G. Kilburn and B. H. Levelton, 10: 427.

Continuous Lamination of Lumber, N. Malarkey, Jr., 2: 68.

High Speed Drying of Western Softwoods for Exterior Plywood, F. H. Milligan and R. D. Davies, 1: 23.

Improvement of Sawmill Cutting Tool Sharp Life by Surface Hardening, H. N. Halvorson and W. M. Stuart, 3: 108.

Precompressing Flitches to Improve the Quality of Slicewood, J. F. Lutz, 6: 248.

Ventilating Veneer Dryers, S. E. Corder, 10: 449.

Progress in Chemical Conversion, J. W. Rowe, 7: 276.

Progress in Logging: 1962–1963: Mechanization Increases Production, George Stenzel, 11: 463.

Pulp Liquors

Investigation of Solvent Extractives from NSSC Black Liquor, W. A. Biggs, W. R. Cook, and I. A. Pearl, 10: 433.

Pulping: See Chemical Conversion.

Polyethylene Glycol

Q

Quality and Strength Properties of Douglas-fir Dried at High Temperatures, M. Salamon, 8: 339.

Quality Control: See Production Management.

R

Radio Frequency Heating: See also Glues and Gluing Processes.

Durability of R. F. Cured Urea Bonds, R. W. Peterson, 5: 187.

New Method for Selecting Glues for R. F. Heating, J. F. S. Carruthers, 5: 190.

Radioactive Wastes

Exploratory Experiments on the Possible Use of Radioactive Waste Materials in Wood Industries, N. C. Franz, 3: 94.

Reactions of Ethyleneimine with Alkali Lignins, J. B. Doughty, 9: 413.

Resource Allocation in the Wood Industry, P. J. Dyson, 8: 337.

Role of Temperature in the Relief of Drying Stresses, D. E. Nelson, 3: 124.

Roll Gluing of Exterior Overlays, A L. Mottet, D. Burnet, R. Casselman, and E. Heller, 5: 175.

S

Sandwich Construction: See Glues and Gluing Processes and Wood Engineering.

Selected Wood Characteristics of Young Yellow Poplar, I: A. C. Barefoot, Jr., 6: 233.

Selected Wood Characteristics of Young Yellow Poplar (*Liriodendron tulipifera* L.), II: Shrinkage of Normal and Abnormal Wood, 10: 443.

Significance of Microshrinkage During the Initial Stages of Drying, J. G. Haygreen, 12: 533.

Siliceous Skeletons of Wood Fibers, R. M. Chatters, 9: 368.

Slash Pine

Impact of Naval Stores on Utilization of Longleaf and Slash Pine Timber, R. H. Page, 9: 361.

Slicewood

Precompressing Flitches to Improve the Quality of Slicewood, J. F. Lutz, 6: 248.

Small Dry Kiln, J. P. Howe and W S. McNamara, 9: 417.

Softwoods, Western

Compressibility and Bond Quality of Western Softwood Veneers, R. A. Currier, 2: 71.

High Speed Drying of Western Softwoods for Exterior Plywood, F. H. Milligan and R. D. Davies, 1: 23.

Soil Conditioners: See also Bark and Chemical Conversion

Fortified Bark for Mulching and Soil Conditioning, W. B. Bollen and D. W. Glennie, 6: 209.

Some Engineering Considerations of a Wood-Chip Pipeline, W. A. Hunt, 9: 365.

Some Observations on the Development of a Laboratory Flakeboard Process, C. A. Hart and J. T. Rice, 11: 483.

Southern Pine Plywood

Technical Considerations for Manufacturing Southern Pine Plywood, H. O. Fleischer and J. F. Lutz, 1: 39.

Specific Heat and Conductivity of Particleboard as Functions of Temperature, R. J. Ward and C. Skaar, 1: 31.

Spiral Grain in Trees, A Review, A. F. Noskowiak, 7: 266.

Status of Structural Design for Light Frame Structures, D. H. Percival, 7: 260.

Storage-Rot Fungi

Effect of a Mold, *Trichoderma Viride*, On Decay of Birch by Four Storage-Rot Fungi, J. K. Shields and E. A. Atwell, 7: 262.

Stress Relief: See also Drying.

Role of Temperature in the Relief of Drying Stresses, D. E. Nelson, 3: 124.

Structural Fastenings: See Wood Engineering.

Structural Sandwiches: See Glues and Gluing Processes and Wood Engineering.

Studies on Predrying and Polyethylene Glycol Treatment of Green Oak, H. A. Huber and A. W. Klimaszewski, 10: 430.

Surface Checking of White Oak As Related to Mechanical Processing, L. I. Gaby, 12: 529.

Surface Texture Measurements, D. A. Stumbo, 7: 299.

T

Technical Considerations for Manufacturing Southern Pine Plywood, H. O. Fleischer and J. F. Lutz, 1: 39.

Telegraphing

Surface Texture Measurements, D. A. Stumbo, 7: 299.

Ten Ways to Up-Date Preventive Maintenance, T. J. Sievert, 4: 139.

Tensile Strength Test for Comparative Evaluation of Wood Preservatives, F. L. Brown, 9: 405.

Testing Decay Resistance of Vapor-Retarding Ground Covers, R. C. Scheffer and J. W. Clark, 8: 330.

Thermal Properties of Bark, R. E. Martin, 10: 419.

Timber Connectors: See also Wood Engineering and Drying

Effect of Moisture Content on Strength of Bolted Timber Connection, J. Longworth and A. E. McMullin, 3: 104.

TIMBER PRODUCTION

Progress in Logging, 1962–1963: Mechanization Increases Production, George Stenzel, 11: 463.

Forest Economics

Evaluating Log and Tree Quality for Wood Products, P. H. Lane, 3: 89.

Integrated Marketing by Non-Integrated Timber Owners, M. P. Lazara, 4: 147.

Woods Mechanization

Wheel Tractor Logging, F. C. Simmons, 8: 313.

Time-Related Flexural Behavior of Small Douglas-Fir Beams Under Prolonged Loading, R. L. Youngs and H. C. Hilbrand, 6: 227.

Tomorrow's Houses from Trees of Today, O. C. Heyer, 6: 252.

Tracheids

Characteristics of Tracheids Produced in Gamma and Gamma-Neutron Environment, J. R. Hamilton, 2: 62.

Transverse Shrinkage of Wood, W. C. Stevens, 9: 386.

TREATMENTS AND COATINGS

Dimensional Stabilization with Polymerizable Vapor of Ethylene Oxide, C. W. McMillin, 2: 56.

Exterior Finishing

Weathering Resistance of Plywood Bonded and Coated with Phenol Formaldehyde, H. H. Bosshard and L. P. Futo, 12: 557.

Fire Resistance

Gluability of Fire-Retardant Treated Wood, E. G. Bergin, 12: 549.

Preservation

Analysis of Creosote by Infrared Spectroscopy, R. W. Drisko, 4: 156.

Beetle Scars in Philippine Mahogany, G. N. Arneson, 4: 149.

Effect of a Mold, *Trichoderma Viride*, On Decay of Birch by Four Storage-Rot Fungi, J. K. Shields and E. A. Atwell, 7: 262.

Effect of Gamma Radiation on Decay Resistance of Wood, T. C. Scheffer, 5: 208.

Effect of Treating Conditions on Dimensional Behavior of Wood During Polyethylene Glycol Soak Treatments, D. L. Kenaga, 8: 345.

Fumigation May End Oak Embargoes, T. W. Jones, 12: 564.

On-Site Preservative Treatments: Their Effectiveness for Exterior Millwork of Different Species Used in Various Climates, R. C. Scheffer, A. F. Verral, and G. Harvey, 1: 7.

Overtreatment of Millwork: Is Control at the Log Pond Feasible?, M. D. MacPeak, 4: 142.

PEG-Treated Walnut Limbwood Makes Handsome Decorator Clock, H. L. Mitchell, 9: 416.

Studies on Predrying and Polyethylene Glycol Treatment of Green Oak, H. A. Huber and A. W. Klimaszewski, 10: 430.

Tensile Strength Test for Comparative Evaluation of Wood Preservatives, F. L. Brown, 9: 405.

Testing Decay Resistance of Vapor-Retarding Ground Covers, R. C. Scheffer and J. W. Clark, 8: 330.

Water-Repellent Preservatives on Exterior Woodwork of Buildings, A. F. Verrall, 10: 460.

Trichoderma Viride

Effect of a Mold, *Trichoderma Viride*, On Decay of Birch by Four Storage-Rot Fungi, J. K. Shields and E. A. Atwell, 7: 262.

Two Views on Research, R. J. Anderson and R. J. Seidl, 12: 525.

U

Urea Resins: See also Glues and Gluing

Efficiency of Urea- and Phenol-Formaldehyde in Particleboard, M. Carroll, 3: 113.

V

Vapor Barriers

Testing Decay Resistance of Vapor-Retarding Ground Covers, R. C. Scheffer and J. W. Clark, 8: 330.

Veneer: See Glues and Gluing Processes and Drying.

Veneer and Plywood, book review by H. O. Fleischer, 5: 186.

Veneer Cutting: See Mechanical Conversion.

Ventilating Veneer Dryers, S. E. Corder, 10: 449.

W

Wafer Dimension Control: Number One Design Criterion for Plant Producing Particleboard for Building Construction Uses, J. M. Gunn, 4: 163.

Water-Repellents: See also Treatments and Coatings

On-Site Preservative Treatments: Their Effectiveness for Exterior Millwork of Different Species Used in Various Climates, R. C. Scheffer, A. F. Verrall, and G. Harvey, 1: 7.

Overtreatment of Millwork: Is Control at the Log Pond Feasible?, M. D. MacPeak, 4: 142.

Water-Repellent Preservatives on Exterior Woodwork of Buildings, A. F. Verrall, 10: 460.

Weathering Resistance of Plywood Bonded and Coated with Phenol Formaldehyde, H. H. Bosshard and L. P. Futo, 12: 557.

Wheel Tractor Logging, F. C. Simmons, 8: 313.

Wood–Aluminum Beams Within and Beyond the Elastic Range—Part II: Trapezoidal Sections, Richard Mark, 11: 508.

Wood-Chip Pipeline

Some Engineering Considerations of a Wood-Chip Pipeline, W. A. Hunt, 9: 365.

WOOD ENGINEERING

Bright Future for Wood Engineering, A. P. Schniewind, 8: 323.

Engineered Products

Continuous Lamination of Lumber, N. Malarkey, Jr., 2: 68.

Design of Plywood Folded Plates, D. H. Brown, 4: 131.

New Method for Testing Glue Joints of Laminated Timbers, M. L. Selbo, 3: 93.

Production and Marketing of Plywood Structural Components, K. M. Watson, 8: 319.

Status of Structural Design for Light Frame Structures, D. H. Percival, 7: 260.

Testing Decay Resistance of Vapor-Retarding Ground Covers, R. C. Scheffer and J. W. Clark, 8: 330.

Tomorrow's Houses from Trees of Today, O. C. Heyer, 6: 252.

Wood–Aluminum Beams Within and Beyond the Elastic Range—Part II: Trapezoidal Sections, Richard Mark, 11: 508.

Mechanical Properties

After Lumber — What Other Products — Why?, H. B. McKean, 5: 180.

Piezoelectric Effect in Wood, W. L. Galligan and L. D. Bertholf, 12: 517.

Time-Related Flexural Behavior of Small Douglas-Fir Beams Under Prolonged Loading, R. L. Youngs and H. C. Hilbrand, 6: 227.

Structural Fastenings

Effect of Joint Geometry on Tensile Strength of Finger Joints, M. L. Selbo, 9: 390.

Effect of Moisture Content on Strength of Bolted Timber Connection, J. Longworth and A. E. McMullin, 3: 104.

Wood Quality: See Also Anatomy and Fundamental Properties

Abnormal Wood in Yellow Poplar: (*Liriodendron Tulipifera* L.), A. C. Barefoot, Jr., 1: 16.

Evaluating Log and Tree Quality for Wood Products, P. H. Lane, 3:89.

Internal Moisture Stress and Wood Formation in Conifers, R. Zahner, 6: 240.

Peculiarity of Compression of Conifers in Radial Direction, J. Bodig, 10: 438.

Quality and Strength Properties of Douglas-fir Dried at High Temperatures, M. Salamon, 8: 339.

Selected Wood Characteristics of Young Yellow Poplar, A. C. Barefoot Jr., 6: 233.

Selected Wood Characteristics of Young Yellow Poplar: *Liriodendron tulipifera* L.), II: Shrinkage of Normal and Abnormal Wood, 10: 443.

Spiral Grain in Trees, A Review, A. F. Noskowiak, 7: 266.

Wood Structure: See Anatomy and Fundamental Properties.

Woods Mechanization: See Timber Production.

Y

Yellow Poplar

Abnormal Wood in Yellow Poplar: (*Liriodendron Tulipifera* L.), A. C. Barefoot, Jr., 1: 16.

Selected Wood Characteristics of Young Yellow Poplar, A. C. Barefoot, Jr., 6: 233.

Selected Wood Characteristics of Young Yellow Poplar (*Liriodendron tulipifera* L.), II: Shrinkage of Normal and Abnormal Wood, 10: 443.

FPRS Author Index . . . Volume XIII, 1963

A

Anderson, R. J., Two Views on Research: Which Way Is Up?, 12: 525. (No. 3161—$.80)
Arneson, G. N., Beetle Scars in Philippine Mahogany, 4: 149. (No. T-N-10—$.20)
Ashby, M. L., *see* Weakley, F. P.
Atwell, E. A., *see* Shields, J. K.

B

Barefoot, A. C., Jr., Abnormal Wood in Yellow Poplar: (*Liriodendron Tulipifera* L.), 1: 16. (No. 2076—$1.40)
Barefoot, A. C., Jr., Selected Wood Characteristics of Young Yellow Poplar, I, 6: (No. 2085—$1.40)
Barefoot, A. C., Jr., Selected Wood Characteristics of Young Yellow Poplar (*Liriodendron tulipifera* L.), II: Shrinkage of Normal and Abnormal Wood, 10: 443. (No. 3083—$1.20)
Barton, G. M., Conidendrin in the Floccosoids of Western Hemlock, 7: 304. (No. TN-25—$.20)
Barton, G. M., and J. A. F. Gardner, Color Precursors in Douglas-Fir, 6: 216. (No. 3036—$1.00)
Behr, E. A., Cell-Wall Model, 4: 168. (No. TN-6—$.20)
Bergin, E. G., Gluability of Fire-Retardant Treated Wood, 12: 549. (No. 3105—$1.50)
Bertholf, L. D., *see* Galligan, W. L.
Biggs, W. A., W. R. Cook, and I. A. Pearl, Investigation of Solvent Extractives from NSSC Black Liquor, 10: 433. (No. 3112—$1.00)
Black, J. M. *see* Hann, R. A.
Blomquist, R. F., *see* Hann, R. A.
Bodig, J., The Peculiarity of Compression of Conifers in Radial Direction, 10: 438. (No. TN-29—$.20)
Bollen, W. B., and D. W. Glennie, Fortified Bark for Mulching and Soil Conditioning, 6: 209. (No. 3085—$1.40)
Bosshard, H. H., and L. P. Futo, Weathering Resistance of Plywood Bonded and Coated with Phenol Formaldehyde, 12: 557. (No. 3216—$1.00)
Brown, D. H., Design of Plywood Folded Plates, 4: 131. (No. 3024—$1.50)
Brown, F. L., Tensile Strength Test for Comparative Evaluation of Wood Preservatives, 9: 405. (No. 3123—$1.50)
Brown, J. H., R. W. Davidson, and C. Skaar, The Mechanism of Electrical Conduction in Wood, 10: 455. (No. 3140—$1.00)
Bryan, E. L., High Energy Jets as a New Concept in Wood Machining, 8: 305. (No. 3115—$1.50)
Bryan, E. L., Machining Wood with Light, 1: 14. (TN-11—$.20)
Burnet, Don, *see* Mottet, A. L.

C

Carroll, M., Efficiency of Urea- and Phenol-Formaldehyde in Particleboard, 3: 113. (No. 3002—$1.50)
Carruthers, J. F. S., A New Method for Selecting Glues for R. F. Heating, 5: 190. (No. 3060—$1.00)
Casselmann, R., *see* Mottet, A. L.
Chatters, R. M., Siliceous Skeletons of Wood Fibers, 9: 368. (No. 3058—$1.00)
Choong, E. T., Movement of Moisture through a Softwood in the Hygroscopic Range, 11: 489. (No. 3061—$1.50)
Clark, J. W., *see* Scheffer, J. C.
Comstock, G. L., Moisture Diffusion Coefficients in Wood as Calculated from Adsorption, Desorption, and Steady State Data, 3: 97. (No. 3005—$1.40)
Cook, W. R., *see* Biggs, W. A.
Corder, S. E., Ventilating Veneer Dryers, 10: 449. (No. 3111—$1.00)
Currier, R. A., Compressibility and Bond Quality of Western Softwood Veneers, 2: 71. (No. 2093—$1.50)

D

Davidson, R. W., *see* Brown, J. H.
Davies, R. D., *see* Milligan, F. H.
Doughty, J. B., Reactions of Ethyleneimine with Alkali Lignins, 9: 413. (No. 3148—$.60)
Drisko, R. W., Analysis of Creosote by Infrared Spectroscopy, 4: 156. (No. 3034—$1.40)
Dyson, P. J., Resource Allocation in the Wood Industry, 8: 337. (No. 3149-B—$.40)

E

Ecklund, B. A., *see* Ellwood, E. L.
Ecklund, B. A., *see* Resch, Helmuth
Ellwood, E. L., and B. A. Ecklund, Effect of Organic Liquids on Collapse and Shrinkage of Wood, II. Effect of Degree of Replacement, 7: 291. (No. 2031—$1.50)
Ellwood, E. L., and B. A. Ecklund, Effect of Organic Liquids on Collapse and Shrinkage of Wood, II. Effect of Drying Temperature 8: 350. (No. 2031-A—$1.00)
Ellwood, E. L., B. A. Ecklund, and E. Zavarin, Effect of Organic Liquids on Collapse and Shrinkage of Wood, III. Chemical Influences, 9: 401. (No. 2031-C—$.80)
Englerth, G. H., and H. L. Mitchell, New Horizons in Bowl Turning, 2: 48. (No. 3069—$.40)

F

Fleischer, H. O., and J. F. Lutz, Technical Considerations for Manufacturing Southern Pine Plywood, 1: 39. (No. 3054—$.80)
Franz, N. C., Exploratory Experiments on the Possible Use of Radioactive Waste Materials in Wood Industries, 3: 94. (No. 3079—$.60)
Futo, L. P., *see* Bosshard, H. H.

G

Gaby, L. I., Surface Checking of White Oak As Related to Mechanical Processing, 12: 529. (No. 3150—$.80)
Galligan, W. L., and L. D. Bertholf, Piezoelectric Effect in Wood, 12: 517. (No. 3091—$1.50)
Gardner, J. A. F., *see* Barton, G. M.
Glennie, D. W., *see* Bollen, W. B.
Gunn, J. M., Wafer Dimension Control: Number One Design Criterion for Plant Producing Particleboard for Building Construction Uses, 4: 163. (No. 2090—$1.00)

H

Hair, D., Economic Importance of Timber in the United States, 9: 355. (No. 3108—$1.20)
Halvorson, H. N., and W. M. Stuart, Improvement of Sawmill Cutting Tool Sharp Life by Surface Hardening, 3: 108. (No. 2095—$.80)
Hamilton, J. R., A Dual-Linear Micrometer, 2: 70. (No. TN-9—$.20)
Hamilton, J. R., Characteristics of Tracheids Produced in Gamma and Gamma-Neutron Environment, 2: 62. (No. 3041—$1.20)
Hancock, W. V., Effect of Heat Treatment on the Surface of Douglas-Fir Veneer, 2: 81. (No. 3001—$1.50)
Hann, R. A., J. M. Black, and R. F. Blomquist, How Durable is Particleboard?, 5: 169. (No. 3077—$1.20)
Hart, C. A., and J. T. Rice, Some Observations on the Development of a Laboratory Flakeboard Process, 11: 483. (No. 3047A—$1.20)
Harvey, George, *see* Scheffer, T. C.
Haygreen, J. G., The Significance of Microshrinkage During the Initial Stages of Drying, 12: 533. (No. 3147—$1.00)
Heller, E., *see* Mottet, A. L.
Heller, P., Improvement and Automation, 3: 112. (No. TN-17—$.20)
Hemming, C. B., Consolidation & Refinement Mark Progress in Glues & Gluing, 2: 45. (No. 3070—$.60)
Trees of Today, 6: 252. (No. 3021—
Heyer, O. C., Tomorrow's Houses from Trees of Today, 6: 252. (No. 3021—$.60)
Hilbrand, H. C., *see* Youngs, R. L.
Hoadley, R. B., Influence of Certain Variables on Veneer-Cutting Behavior, 12: 538. (No. 3215—$1.50)
Howe, J. P., and W. S. McNamara, A Small Dry Kiln, 9: 417. (No. TN-24A—$.40)
Huber, H. A., and A. W. Klimaszewski, Studies on Predrying and Polyethylene Glycol Treatment of Green Oak, 10: 430. (No. 2060—$.80)
Hunt, W. A., Some Engineering Considerations of a Wood-Chip Pipeline, 9: 365. (No. 3074—$.60)

J

Jones, T. W., Fumigation May End Oak Embargoes, 12: 564. (No. TN-28—$.20)

K

Katz, A. R., and D. G. Miller, Effect of Water Storage on Electrical Resistance of Wood, 7: 255. (No. 3084—$1.00)
Kenaga, D. L., Effect of Treating Conditions on Dimensional Behavior of Wood During Polyethylene Glycol Soak Treatments, 8: 345. (No. 3082—$1.00)
Kilburn, D. G., and B. H. Levelton, Charcoal Production by a Fluid-Bed Process, 10: 427. (No. 3155—$1.20)
Klimaszewski, A. W., *see* Huber, H. A.
Kozlik, Charles J., Developments in Wood Drying, 1: 1. (No. 3053—$1.20)
Kübler, H., Drying in Russia: Research and Practice, 12: 557. (No. 3081—$.40)

L

Lambe, T. A., Analysis of the Productive Capacity of Sawmill Headrigs, 11: 499. (No. 3047—$.80)
Lane, P. H., Evaluating Log and Tree Quality for Wood Products, 3: 89. (No. 3000—$1.00)
Lazara, M. P., Integrated Marketing by Non-Integrated Timber Owners, 4:147. (No. 3069—$.40)
Levelton, B. H., *see* Kilburn, D. G.
Longworth, J., and A. E. McMullin, Effect of Moisture Content on Strength of Bolted Timber Connection, 3: 104. (No. 2068—$.80)
Lowery, D. P., and E. F. Rasmussen, Accelerated Drying of Lodgepole Pine and Western Larch Poles, 6: 221. (No. 3048—$1.20)
Lutz, J. F., Precompressing Flitches to Improve the Quality of Slicewood, 6: 248. (No. TN-12—$.40)
Lutz, J. F., *see* Fleischer, H. O.

M

MacPeak, M. D., Overtreatment of Millwork: Is Control at the Log Pond Feasible?, 4: 142. (No. 2065—$1.00)
Malarkey, Neil, Jr., Continuous Lamination of Lumber, 2: 68. (No. 3043—$.40)
Mark, Richard, Wood–Aluminum Beams Within and Beyond the Elastic Range—Part II: Trapezoidal Sections, 11: 508 (No. 3012—$1.50)
Martin, R. E., Thermal Properties of Bark, 10: 419. (No. 3149—$1.50)
McKean, H. B., After Lumber — What Other Products — Why?, 5: 180. (No. 3088—$1.20)
McMillin, C. W., Dimensional Stabilization with Polymerizable Vapor of Ethylene Oxide, 2: 56. (No. 3039—$1.20)
McMullin, A. E., *see* Longworth, J.
McNamara, W. S., *see* Howe, J. P.
Mehltretter, C. L., *see* Weakley, F. P.
Miller, D. G., *see* Katz, A. R.
Milligan, F. H., and R. D. Davies, High Speed Drying of Western Softwoods for Exterior Plywood, 1: 23. (No. 2054—$1.40)
Mitchell, H. L., PEG-Treated Walnut Limbwood Makes Handsome Decorator Clock, 9: 416. (No. TN-25A—$.20)
Mitchell, H. L., *see* Englerth, G. H.
Mote, C. D., Experimental Analysis of Wood Cutting Tool Stresses, 5: 203. (No. 3010—$1.00)
Mottet, A. L., Don Burnet, R. Casselman, and E. Heller, Roll Gluing of Exterior Overlays 5: 175. (No. 3087—$1.00)
Murphey, W. K., Cell-Wall Crystallinity as a Function of Tensile Strain, 4: 151. (No. 3015—$1.20)

N

Nelson, D. E., The Role of Temperature in the Relief of Drying Stresses, 3: 122. (No. 3038—$1.40)
Noskowiak, A. F., Spiral Grain in Trees, A Review, 7: 266. (No. 3042—$1.50)

P

Page, R. H., Impact of Naval Stores on Utilization of Longleaf and Slash Pine Timber, 9: 361. (No. 3107—$.80)
Pearl, I. A., Annual Review of Lignin Chemistry, 9: 373. (No. 3120—$1.50)
Pearl, I. A., Aspen Bark as a Source of Organic Chemicals, 3: 122. (No. 3078—$.40)
Pearl, I. A., *see* Biggs, W. A.
Percival, D. H., Status of Structural Design for Light Frame Structures, 7: 260. (No. 2072—$.40)
Peterson, R. W., Durability of R. F. Cured Urea Bonds, 5: 187. (No. 2087—$.60)

R

Rasmussen, E. F., *see* Lowery, D. P.
Resch, Helmuth, and B. A. Ecklund, Moisture Content Determination for Wood with Highly Volatile Constituents, 11: 481. (No. TN 27—$.40)
Rice, J. T., *see* Hart, C. A.
Richards, D. B., Improved Tips for Finger Joints, 6: 250. (No. TN-24—$.40)
Rowe, J. W., Progress in Chemical Conversion, 7: 276. (No. 3113—$1.50)

S

Sachs, I. B., Improving the Preparation of Glass Knives for Ultra-Microtomy, 2: 80. (No. TN-8—$.20)
Salamon, M., Quality and Strength Properties of Douglas-fir Dried at High Temperatures, 8: 339. (No. 2058—$1.20)
Scheffer, T. C., A. F. Verral, and George Harvey, On-Site Preservative Treatments: Their Effectiveness for Exterior Millwork of Different Species Used in Various Climates, 1: 7. (No. 3019—$1.40)
Scheffer, T. C., and J. W. Clark, Testing Decay Resistance of Vapor-Retarding Ground Covers, 8: 330. (No. 3149-A—$1.40)
Scheffer, T. C., Effect of Gamma Radiation on Decay Resistance of Wood, 5: 208. (No. TN-19—$.20)
Schniewind, A. P., Bright Future for Wood Engineering, 8: 323. (No. 3119—$1.40)
Schniewind, A. P., Mechanism of Check Formation, 11: 475. (No. 3157—$1.20)
Seidl, R. J., Two Views on Research: Research and Management, 12: 525. (No. 3161—$.80)
Selbo, M. L., Effect of Joint Geometry on Tensile Strength of Finger Joints, 9: 390. (No. 3098—$1.50)
Selbo, M. L., New Method for Testing Glue Joints of Laminated Timbers, 3: 93. (No. TN-15—$.20)
Shields, J. K., and E. A. Atwell, Effect of a Mold, *Trichoderma Viride*, On Decay of Birch by Four Storage-Rot Fungi, 7: 262. (No. 3068—$.80)
Sievert, T. J., Ten Ways to Up-Date Preventive Maintenance, 4: 139. (No. 3049—$.60)
Simmons, F. C., Wheel Tractor Logging, 8: 313. (No. 2096—$1.00)
Skarr, C., *see* Brown, J. H.
Skaar, C., *see* Ward, R. J.
Stamm, A. J., Permeability of Wood to Fluids, 11: 503. (No. 3152—$1.00)
Stenzel, George, Progress in Logging, 1962–1963: Mechanization Increases Production, 11: 463. (No. 3171—$1.50)
Stevens, W. C., The Transverse Shrinkage of Wood, 9: 386. (No. 3146—$.80)
Stuart, W. M., *see* Halvorson, H. N.
Stumbo, D. A., Surface Texture Measurements, 7: 299. (No. 3141—$1.20)
Swan, E. P., Characteristics of a Phlobaphene from Western Red Cedar Bark, 5: 195. (No. 3016—$1.50)

T

Tarkow, H., Asymmetrical Permeability of Composite Laminates, 8: 318. (No. TN-20— $.20)

V

Verrall, A. F., Water-Repellent Preservatives on Exterior Woodwork of Buildings, 10: 460. (No. 3121—$.60)
Verral, A. F., *see* Scheffer, T. C.

W

Ward, R. J., and C. Skaar, Specific Heat and Conductivity of Particleboard as Functions of Temperature, 1: 31. (No. 2046—$1.50)
Watson, K. M., Production and Marketing of Plywood Structural Components, 8: 319. (No. 3064—$.80)
Weakley, F. P., M. L. Ashby, and C. L. Mehltretter, Casein-Dialdehyde Starch Adhesive for Wood, 2: 51. (No. 3046—$1.20)

Y

Youngs, R. L., and H. C. Hilbrand, Time-Related Flexural Behavior of Small Douglas-Fir Beams Under Prolonged Loading, 6: 227. (No. 3086—$1.20)

Z

Zahner, R., Internal Moisture Stress and Wood Formation in Conifers, 6: 240. (No. 3035—$1.50)
Zavarin, E., *see* Ellwood, E. L.